

100

Figure 1A



Figure 1B



Figure 1C



Figure 1D

Calculation of [redacted] memory cell retention charact[redacted]tics

q0, C	m0, kg	kb, J/K	h, J-s	hb, J-s
1.6022E-019	9.1095E-031	1.38062E-023	6.62617E-034	1.054588E-034

b0, eV (barrier)	εl	mr, effective mass ratio	T, K degree
2.9	3.9	0.5	300

C	b
1.0630E-006	2.3854E+008

Seconds	Time Period
31536000	1 year
94608000	3 years
1.89E+008	6 years
2.84E+017	9 years
3.78E+008	12 years
4.73E+008	15 years
9.08E+009	18 years
6.62E+008	21 years
7.57E+008	24 years
8.51E+008	27 years
9.46E+008	30 years

Lfg um	0.6000	Channel length of floating gate device
Wfg um	1000.0000	Channel width of floating gate device.
Hfg um	0.0900	Thickness of floating gate polysilicon conductor
Wrx um	0.5000	Width of floating gate overlapping shallow trench isolation
Ttunox A	80	Tunnel oxide thickness
Tono A	190	Thickness of Oxide-Nitride-Oxide dielectric between floating gate and control gate for capacitive coupling
Tswox A	300	Thickness of sidewall oxide between floating gate and control gate for sidewall coupling
Xfd um	0.0500	Length of floating gate overlapping drain region of the floating gate MOSFET
Xfs um	0.3500	Length of floating gate overlapping source region of the floating gate MOSFET
Ainj um2	0.0438	Area of the electron tunneling region between the floating gate and the source for resetting the floating gate charge
Cfc fF	1089.5358	Capacitance between the floating gate and the control gate
Cfsx fF	0.4313	Capacitance between the floating gate and the silicon substrate
Cfd fF	0.1078	Capacitance between the floating gate and the drain
Cfs fF	0.7547	Capacitance between the floating gate and the source
Cfg fF	1090.8295	Total floating gate capacitance
Cr,wl	0.9988	Control gate to floating gate coupling ratio
Cr,src	0.0007	Source junction to floating gate coupling ratio
Vt,fg V	0.90	Threshold voltage of floating gate MOSFET
Verase	0.00	Erase voltage applied to the source(not used here, set to zero)
Vfg,ini	-5.00	Initial floating chaged voltage
Va	0.00	Actual erase volatge (equal to applied + charge stored on the floating)
S	3.76E+016	Derived parameter in the floating gate "erase" equation
X	1.27E+011	Derived parameter in the floating gate "erase" equation

t, sec.	Vt,fg
0.00001	5.907
31536000	5.894
63072000	5.882
94608000	5.871
1.26E+008	5.861
1.58E+008	5.852
1.89E+008	5.843
2.21E+008	5.835
2.52E+008	5.827
2.84E+008	5.820
3.15E+008	5.814
3.47E+008	5.807
3.78E+008	5.801
4.1E+008	5.795
4.42E+008	5.790
4.73E+008	5.785
5.05E+008	5.780
5.36E+008	5.775
5.68E+008	5.770
5.99E+008	5.766
6.31E+008	5.762
6.62E+008	5.757
6.94E+008	5.753
7.25E+008	5.750
7.57E+008	5.746
7.88E+008	5.742
8.2E+008	5.739
8.51E+008	5.735
8.83E+008	5.732
9.15E+008	5.729
9.46E+008	5.726



Figures 1E-1F

Calculation of [redacted] memory cell retention chara[redacted]ristics

q0, C	m0, kg	kb, J/K	h, J-s	hb, J-s
1.6022E-019	9.1095E-031	1.38062E-023	6.62617E-034	**********

b0, eV (barrier)	ε1	mr, effective mass ratio	T, K degree
2.9	3.9	0.5	300

C	b
1.0630E-006	2.3854E+008

Seconds	Time Period
60	1 minute
3600	1 hour
86400	1 day
604800	1 week
2592000	1 month
**********	1 year
**********	4 years
**********	16 years
**********	32 years

Lfg um	0.6000	Channel length of floating gate device
Wfg um	1000.0000	Channel width of floating gate device.
Hfg um	0.0900	Thickness of floating gate polysilicon conductor
Wrx um	0.5000	Width of floating gate overlapping shallow trench isolation
Ttunox A	80	Tunnel oxide thickness
Tono A	190	Thickness of Oxide-Nitride-Oxide dielectric between floating gate and control gate for capacitive coupling
Tswox A	300	Thickness of sidewall oxide between floating gate and control gate for sidewall coupling
Xfd um	0.0500	Length of floating gate overlapping drain region of the floating gate MOSFET
Xfs um	0.3500	Length of floating gate overlapping source region of the floating gate MOSFET
Ainj um2	0.0438	Area of the electron tunneling region between the floating gate and the source for resetting the floating gate charge
Cfc fF	1089.5358	Capacitance between the floating gate and the control gate
Cfsx fF	0.4313	Capacitance between the floating gate and the silicon substrate
Cfd fF	0.1078	Capacitance between the floating gate and the drain
Cfs fF	0.7547	Capacitance between the floating gate and the source
Cfg fF	1090.8295	Total floating gate capacitance
Cr,wl	0.9988	Control gate to floating gate coupling ratio
Cr,src	0.0007	Source junction to floating gate coupling ratio
Vt,fg V	0.90	Threshold voltage of floating gate MOSFET
Verase	0.00	Erase voltage applied to the source(not used here, set to zero)
Vfg,ini	-5.00	Initial floating chaged voltage
Vd	0.00	Actual erase volatge (equal to applied + charge stored on the floating)
S	3.76E+016	Derived parameter in the floating gate "erase" equation
X	1.27E+011	Derived parameter in the floating gate "erase" equation

t, sec.	Vt,fg
0.00001	5.907
2	5.907
4	5.907
8	5.907
16	5.907
32	5.907
64	5.907
128	5.907
256	5.907
512	5.907
1024	5.907
2048	5.907
4096	5.907
8192	5.907
16384	5.907
32768	5.907
65536	5.907
131072	5.907
262144	5.907
524288	5.907
1000000	5.907
2000000	5.906
4000000	5.905
8000000	5.904
16000000	5.900
32000000	5.894
64000000	5.881
**********	5.860
**********	5.827
**********	5.779
**********	5.718



Figures 1G-1H

Calculation of [redacted] memory cell retention characteristics

q0, C	m0, kg	kb, J/K	h, J-s	hb, J-s
1.6022E-019	9.1095E-031	1.38062E-023	6.62617E-034	**********

b0, eV (barrier)	ε1	mr, effective mass ratio	T, K degree
2.9	3.9	0.5	300

C	b
1.0630E-006	2.3854E+008

Seconds	Time Period
60	1 minute
3600	1 hour
86400	1 day
604800	1 week
2592000	1 month
**********	1 year
**********	4 years
**********	16 years
**********	32 years

Lfg um	0.6000	Channel length of floating gate device
Wfg um	1000.0000	Channel width of floating gate device.
Hfg um	0.0900	Thickness of floating gate polysilicon conductor
Wrx um	0.5000	Width of floating gate overlapping shallow trench isolation
Ttunox A	85	Tunnel oxide thickness
Tono A	190	Thickness of Oxide-Nitride-Oxide dielectric between floating gate and control gate for capacitive coupling
Tswox A	300	Thickness of sidewall oxide between floating gate and control gate for sidewall coupling
Xfd um	0.0500	Length of floating gate overlapping drain region of the floating gate MOSFET
Xfs um	0.3500	Length of floating gate overlapping source region of the floating gate MOSFET
Ainj um2	0.0438	Area of the electron tunneling region between the floating gate and the source for resetting the floating gate c
Cfc fF	1089.5358	Capacitance between the floating gate and the control gate
Cfsx fF	0.4059	Capacitance between the floating gate and the silicon substrate
Cfd fF	0.1015	Capacitance between the floating gate and the drain
Cfs fF	0.7103	Capacitance between the floating gate and the source
Cfg fF	1090.7534	Total floating gate capacitance
Cf,wl	0.9989	Control gate to floating gate coupling ratio
Cf,src	0.0007	Source junction to floating gate coupling ratio
Vt,fg V	0.90	Threshold voltage of floating gate MOSFET
Verase	0.00	Erase voltage applied to the source(not used here, set to zero)
Vfg,ini	-5.00	Initial floating chaged voltage
Va	0.00	Actual erase volatge (equal to applied + charge stored on the floating)
S	4.09E+017	Derived parameter in the floating gate "erase" equation
X	1.20E+011	Derived parameter in the floating gate "erase" equation

t, sec.	Vt,fg
0.00001	5.907
2	5.907
4	5.907
8	5.907
16	5.907
32	5.907
64	5.907
128	5.907
256	5.907
512	5.907
1024	5.907
2048	5.907
4096	5.907
8192	5.907
16384	5.907
32768	5.907
65536	5.907
131072	5.907
262144	5.907
524288	5.907
1000000	5.907
2000000	5.907
4000000	5.906
8000000	5.906
1.6E+007	5.906
3.2E+007	5.905
6.4E+007	5.904
**********	5.902
**********	5.898
**********	5.889
**********	5.874



Figures 1I-1J


Increasing time
Decreasing floating gate charge
I_{Drain}
Decreasing $V_{Theshold}$
V_{Read}
V_{Gate}

Figure 1K

Calculation of time cell retention characteristics

q0, C	m0, kg	kb, J/K	h, J-s	hb, J-s
1.6022E-019	9.1095E-031	1.38062E-023	6.62617E-034	**********

b0, eV (barrier)	εl	mr, effective mass ratio	T, K degree
2.9	3.9	0.5	300

C	b
1.0630E-006	2.3854E+008

Seconds	Time Period
2592000	1 month
5184000	2 months
7776000	3 months
**********	4 months
**********	5 months
**********	6 months
**********	7 months
**********	8 months
**********	9 months
**********	10 months
**********	11 months
**********	12 months
**********	13 months
**********	14 months
**********	15 months
**********	16 months

Lfg um	0.6000	Channel length of floating gate device
Wfg um	1000.0000	Channel width of floating gate device.
Hfg um	0.0900	Thickness of floating gate polysilicon conductor
Wrx um	0.5000	Width of floating gate overlapping shallow trench isolation
Ttunox A	65	Tunnel oxide thickness
Tono A	190	Thickness of Oxide-Nitride-Oxide dielectric between floating gate and control gate for capacitive coupling
Tswox A	300	Thickness of sidewall oxide between floating gate and control gate for sidewall coupling
Xfd um	0.0500	Length of floating gate overlapping drain region of the floating gate MOSFET
Xfs um	0.3500	Length of floating gate overlapping source region of the floating gate MOSFET
Ainj um2	0.0438	Area of the electron tunneling region between the floating gate and the source for resetting the floating gate charge
Cfc fF	1089.5358	Capacitance between the floating gate and the control gate
Cfsx fF	0.5308	Capacitance between the floating gate and the silicon substrate
Cfd fF	0.1327	Capacitance between the floating gate and the drain
Cfs fF	0.9288	Capacitance between the floating gate and the source
Cfg fF	1091.1281	Total floating gate capacitance
Cr,wl	0.9985	Control gate to floating gate coupling ratio
Cfsrc	0.0009	Source junction to floating gate coupling ratio
Vt,fg V	0.90	Threshold voltage of floating gate MOSFET
Verase	0.00	Erase voltage applied to the source(not used here, set to zero)
Vfg,ini	-5.00	Initial floating chaged voltage
Va	0.00	Actual erase volatge (equal to applied + charge stored on the floating)
S	2.93E+013	Derived parameter in the floating gate "erase" equation
X	1.56E+011	Derived parameter in the floating gate "erase" equation

t, sec.	Vt,fg
0.00001	5.909
1296000	5.596
2592000	5.508
3888000	5.456
5184000	5.420
6480000	5.392
7776000	5.369
9072000	5.349
**********	5.333
**********	5.318
1.3E+007	5.305
**********	5.293
**********	5.283
**********	5.273
**********	5.264
**********	5.256
**********	5.248
2.2E+007	5.240
**********	5.234
**********	5.227
**********	5.221
**********	5.215
**********	5.210
**********	5.204
**********	5.199
**********	5.195
**********	5.190
3.5E+007	5.185
**********	5.181
**********	5.177
**********	5.173



Figures 1L-1M

Calculation of time cell retention characteristics

q0, C	m0, kg	kb, J/K	h, J-s	hb, J-s
1.6022E-019	9.1095E-031	1.38062E-023	6.62617E-034	1.054588E-034

b0, eV (barrier)	εl	mr, effective mass ratio	T, K degree
2.9	3.9	0.5	300

C	b
1.0630E-006	2.3854E+008

Seconds	Time Periods
60	1 minute
3600	1 hour
86400	1 day
604800	1 week
1209600	2 weeks
2592000	1 month
5184000	2 months
10368000	4 months
15552000	6 months
20736000	8 months
25920000	10 months
31104000	12 months
36288000	14 months
41472000	16 months

Lfg um	0.6000	Channel length of floating gate device
Wfg um	1000.0000	Channel width of floating gate device.
Hfg um	0.0900	Thickness of floating gate polysilicon conductor
Wrx um	0.5000	Width of floating gate overlapping shallow trench isolation
Ttunox A	65	Tunnel oxide thickness
Tono A	190	Thickness of Oxide-Nitride-Oxide dielectric between floating gate and control gate for capacitive coupling
Tswox A	300	Thickness of sidewall oxide between floating gate and control gate for sidewall coupling
Xfd um	0.0500	Length of floating gate overlapping drain region of the floating gate MOSFET
Xfs um	0.3500	Length of floating gate overlapping source region of the floating gate MOSFET
Ainj um2	0.0438	Area of the electron tunneling region between the floating gate and the source for resetting the floating gate charge
Cfc fF	1089.5358	Capacitance between the floating gate and the control gate
Cfsx fF	0.5308	Capacitance between the floating gate and the silicon substrate
Cfd fF	0.1327	Capacitance between the floating gate and the drain
Cfs fF	0.9288	Capacitance between the floating gate and the source
Cfg fF	1091.1281	Total floating gate capacitance
Cr,wl	0.9985	Control gate to floating gate coupling ratio
Cr,src	0.0009	Source junction to floating gate coupling ratio
Vt,fg V	0.90	Threshold voltage of floating gate MOSFET
Verase	0.00	Erase voltage applied to the source(not used here, set to zero)
Vfg,ini	-5.00	Initial floating chaged voltage
Va	0.00	Actual erase volatge (equal to applied + charge stored on the floating)
S	2.93E+013	Derived parameter in the floating gate "erase" equation
X	1.56E+011	Derived parameter in the floating gate "erase" equation

t, sec.	Vt,fg
0.00001	5.909
2	5.909
4	5.909
8	5.909
16	5.909
32	5.909
64	5.909
128	5.909
256	5.908
512	5.908
1024	5.908
2048	5.907
4096	5.905
8192	5.902
16384	5.895
32768	5.883
65536	5.861
131072	5.824
262144	5.771
524288	5.702
604800	5.686
1209600	5.604
2592000	5.508
5184000	5.420
10368000	5.333
15552000	5.283
20736000	5.248
25920000	5.221
31104000	5.199
36288000	5.181
41472000	5.166



Figures 1N-1O

Calculation of time cell retention characteristics

q0, C	m0, kg	kb, J/K	h, J-s	hb, J-s
1.6022E-019	9.1095E-031	1.38062E-023	6.62617E-034	**********

b0, eV (barrier)	εl	mr, effective mass ratio	T, K degree
2.9	3.9	0.5	300

C	b
1.0630E-006	2.3854E+008

Seconds	Time Period
60	1 minute
3600	1 hour
86400	1 day
604800	1 week
1209600	2 weeks
2592000	1 month
5184000	2 months
**********	4 months
**********	6 months
**********	8 months
**********	10 months
**********	12 months
**********	14 months
**********	16 months

Lfg um	0.6000	Channel length of floating gate device
Wfg um	1000.0000	Channel width of floating gate device.
Hfg um	0.0900	Thickness of floating gate polysilicon conductor
Wrx um	0.5000	Width of floating gate overlapping shallow trench isolation
Ttunox A	60	Tunnel oxide thickness
Tono A	190	Thickness of Oxide-Nitride-Oxide dielectric between floating gate and control gate for capacitive coupling
Tswox A	300	Thickness of sidewall oxide between floating gate and control gate for sidewall coupling
Xfd um	0.0500	Length of floating gate overlapping drain region of the floating gate MOSFET
Xfs um	0.3500	Length of floating gate overlapping source region of the floating gate MOSFET
Ainj um2	0.0438	Area of the electron tunneling region between the floating gate and the source for resetting the floating gate charge
Cfc fF	1089.5358	Capacitance between the floating gate and the control gate
Cfsx fF	0.5750	Capacitance between the floating gate and the silicon substrate
Cfd fF	0.1438	Capacitance between the floating gate and the drain
Cfs fF	1.0063	Capacitance between the floating gate and the source
Cfg fF	1091.2608	Total floating gate capacitance
Cr,wl	0.9984	Control gate to floating gate coupling ratio
Cr,src	0.0009	Source junction to floating gate coupling ratio
Vt,fg V	0.90	Threshold voltage of floating gate MOSFET
Verase	0.00	Erase voltage applied to the source(not used here, set to zero)
Vfg,ini	-5.00	Initial floating chaged voltage
Va	0.00	Actual erase volatge (equal to applied + charge stored on the floating)
S	2.70E+012	Derived parameter in the floating gate "erase" equation
xj	1.69E+011	Derived parameter in the floating gate "erase" equation

t, sec.	Vt,fg
0.00001	5.909
2	5.909
4	5.909
8	5.909
16	5.909
32	5.909
64	5.909
128	5.908
256	5.907
512	5.904
1024	5.898
2048	5.888
4096	5.870
8192	5.838
16384	5.789
32768	5.721
65536	5.639
131072	5.549
262144	5.455
524288	5.360
604800	5.341
1209600	5.250
2592000	5.152
5184000	5.067
**********	4.985
**********	4.938
**********	4.906
**********	4.881
**********	4.861
**********	4.844
**********	4.830



Figures 1P-1Q



Figure 2A



Figure 2B



Figure 2C


Programming Request Processing Unit 322
Initialization Request 324
Time Request 328
Time Detection Unit 326
Time Cell Interface Unit 320
[1 week] Time Cell #0 301
[2 weeks] Time Cell #1 302
[3 weeks] Time Cell #2 303
[4 weeks] Time Cell #3 304
[5 weeks] Time Cell #4 305
[6 weeks] Time Cell #5 306
[7 weeks] Time Cell #6 307
[8 weeks] Time Cell #7 308
[3 months] Time Cell #8 309
[4 months] Time Cell #9 310
[5 months] Time Cell #10 311
[6 months] Time Cell #11 312
[9 months] Time Cell #12 313
[12 months] Time Cell #13 314
[15 months] Time Cell #14 315
[18 months] Time Cell #15 316

Figure 3A


Time Set Identifier Unit 348
Time Cell Interface Unit 330
[1 week] Time Cell #0 331
[2 weeks] Time Cell #1 332
[3 weeks] Time Cell #2 333
[4 weeks] Time Cell #3 334
[1 week] Time Cell #4 335
[2 weeks] Time Cell #5 336
[3 weeks] Time Cell #6 337
[4 weeks] Time Cell #7 338
[2 months] Time Cell #8 339
[4 months] Time Cell #9 340
[6 months] Time Cell #10 341
[8 months] Time Cell #11 342
[2 months] Time Cell #12 343
[4 months] Time Cell #13 344
[6 months] Time Cell #14 345
[8 months] Time Cell #15 346

Figure 3B


Time Set Identifier Unit 368
Time Cell Interface Unit 350
[1 month] Time Cell #0 351
[1 month] Time Cell #1 352
[1 month] Time Cell #2 353
[1 month] Time Cell #3 354
[1 month] Time Cell #4 355
[1 month] Time Cell #5 356
[1 month] Time Cell #6 357
[1 month] Time Cell #7 358
[1 month] Time Cell #8 359
[1 month] Time Cell #9 360
[1 month] Time Cell #10 361
[1 month] Time Cell #11 362
[1 month] Time Cell #12 363
[1 month] Time Cell #13 364
[1 month] Time Cell #14 365
[1 month] Time Cell #15 366

Figure 3C



Figure 3D



Figure 3E



Figure 3F



Figure 4A



Figure 4B

Voltages during programming operation



Figure 4C

Voltages during sensing operation



Figure 4D



Figure 4E



Figure 4F


V_{DD}
R_1
R_2
I_1
I_2
V_{OUT}
V_1
V_2
Detector FET
V_{SD}
Chargeloss Sensing FGFET
V_{SG}
V_{SS}

Figure 4G



Figure 4H



Figure 4I



Figure 4J



Figure 4K



Figure 4L



Figure 4M



Figure 4N



Figure 4O



Figure 4P